

DECLARATION OF PERFORMANCE

Product name: Bona SuperSport Primer

Producer: Bona AB, Murmansgatan 130, Malmö, Sweden

Product type: a 1-component waterborne primer for untreated wood sports floors

Type of lacquer:	Waterborne 1-component polyurethane dispersion
Solids content:	Approx 32%
VOC:	Max 60g/lit
Dilution:	If required, dilute with Bona Retarder (4%) for a longer open time.
Drying time:	2-3 hours at 20°C/60% R.H.
Application tools:	Bona Applicator Bar or Bona Roller
Application rate:	8-10 m ² /lit (120-100g/m ²) per coat
Safety	Unclassified
Cleaning:	Wipe tools free from residual material before cleaning with a minimum of water. Dried material can be removed with acetone.
Shelf life:	One year from the date of production in an original unopened container
Storage/transport:	During storage or transport, the temperature must not fall below +5°C or exceed +25°C.
Disposal:	Wastes and emptied containers should be handled by local regulations.
Pack size:	3 x 5 litres (36 boxes per pallet)
Certificates:	GREENGUARD Gold

The information in this document and all other advice and recommendations we provide to help and assist the applicator is based on previous experience and extensive testing but does not claim to be complete. Because of the wide range of possible uses and conditions of application of our products, we do not relieve users from the need to carry out their trials or to seek technical advice from Bona before use. Bona can only guarantee its products and not the construction as a whole. Observe recommendations from flooring manufacturers and the provisions of relevant standards.

Malmö 2023-05-24



Thomas Hallberg

Director Product Management EMEA/PAC

